

Special Order sign light



3 Faces Fire Host



Single Faces Fire Host



Extra Length Fire Exit Light



Extra Width Fire Exit Light

Note : Special Order Sign Light available upon request

Remote Lamp/PLL Type

Wall Mounted



Ceiling Mounted



Transfer Relay



Transfer Relay

The Transfer Relay Kit is designed for Maintained Normal 220 VAC. From main electricity supply and incoming emergency sources i.e. CU SERIES, HP SERIES, PU SERIES.

Specification

Mode of Operation	: Non - Maintained
Main Supply	: (1) AC 220 Volt, 50 Hz, 10% - Single Phase (2) DC 12 / 24 / 220 Volt or AC 220 Volt from CU / HP / PU Series product
Output	: DC 12 / 24 / 220 Volt or AC 220 Volt
Load	: Incandescent, Tungsten Halogen, Dichroic Halogen, Fluorescent, Compact Fluorescent
Construction	: Electro-Galvanized steel sheet 0.9 mm. with epoxy powder and stove enamel coated anti-rust corrosion proof

For PU Series

MODEL	FOR PU SERIES	DIMENSION W x L x H (cm.)	WEIGHT(kg.)
TR-P-220	All Model	17 x 4 x 4.7	0.3

For HP Series

MODEL	FOR PU SERIES	DIMENSION W x L x H (cm.)	WEIGHT(kg.)
TR-H-220	All Model	17 x 4 x 4.7	0.3

For CU Series

MODEL	FOR PU SERIES	DIMENSION W x L x H (cm.)	WEIGHT(kg.)
TR-C-12	CU 12 Volt All Model	17 x 4 x 4.7	0.3
TR-C-24	CU 24 Volt All Model		