

# CP Series



## Specification

Mode of Operation	: Non - Maintained
Lamp	: Tungsten Halogen or Dichroic Halogen, with 180° adjustable sets and plastic-cover anti-dust
Main Supply	: AC 220 Volt, 50 Hz, 10% Single Phase
Construction	: Electro-Galvanized steel sheet 1 mm. with epoxy powder and stove enamel coated anti-rust corrosionproof or ABS Flame Retardant UL 94 V-0
Battery	: Sealed lead acid battery, based on ISO 9001, ISO14001 certified and UL
Charger	: Solid state system automatic battery charger : Constant voltage & current charging systems : SMD electronic part : Switching regulated transforme
Charging Period	: 15-20 Hours as required : Low - High voltage cut-off, preventing battery over charge & discharge
Safety Features	: AC fuse - preventing short circuit and overload for main incoming AC 220 Volt : DC fuse - preventing short circuit and overload for charging & load : AC under voltage protection

**CP Series  
Dichroic Halogen (square)**

MODEL	BATTERY	BULBS (Watt)	DURATION (Hrs. Mins) - +10%	WEIGHT (Kgs)	DIMENSION W x L x H (cm)
CP07	12V. 7.2Ah.	2 x 20 2 x 35	1.40 1.00	4.6	29.5 x 8.5 x 28
CP12	12V. 12Ah.	2 x 20 2 x 35	2.30 1.30	5.8	29.5 x 11 x 28
CP15	12V. 15Ah.	2 x 20 2 x 35 2 x 50 2 x 55	3.30 2.00 1.25 1.15	8.0	37 x 8.5 x 34
CP18	12V. 18Ah.	2 x 35 2 x 50 2 x 55	2.30 1.40 1.30	8.1	
CP21	12V. 21Ah.	2 x 35 2 x 50 2 x 55	2.50 2.00 1.50	9.6	
CP23	12V. 24Ah.	2 x 35 2 x 50 2 x 55	3.15 2.15 2.00	10.0	
CP26	12V. 26Ah.	2 x 35 2 x 50 2 x 55	3.30 2.30 2.15	12.4	
CP35	12V. 35Ah.	2 x 35 2 x 50 2 x 55	4.45 3.20 3.00	14.2	
CP40	12V. 40Ah.	2 x 35 2 x 50 2 x 55	5.15 3.50 3.30	19.1	

**Tungsten Halogen Lamp  
(rectangle □ / Round ○)**

MODEL	BATTERY	BULBS (Watt)	DURATION (Hrs. Mins) - +10%	WEIGHT (Kgs)	DIMENSION W x L x H (cm)
○ CP07	12V. 7.2Ah.	2 x 20 2 x 35	1.40 1.00	5.1	29.5 x 8.5 x 28
○ CP12	12V. 12Ah.	2 x 20 2 x 35	2.30 1.30	6.2	29.5 x 11 x 28
○□ CP15	12V. 15Ah.	2 x 20 2 x 35 2 x 55	3.30 2.00 1.15	8.0	37 x 8.5 x 34
○□ CP18	12V. 18Ah.	2 x 35 2 x 55	2.30 1.30	8.4	37 x 8.5 x 34
○□ CP21	12V. 21Ah.	2 x 35 2 x 55	2.50 1.50	9.6	
○□ CP23	12V. 24Ah.	2 x 35 2 x 55	3.15 2.00	10.0	
○□ CP26	12V. 26Ah.	2 x 35 2 x 55	3.30 2.15	12.4	37 x 18 x 34
○□ CP35	12V. 35Ah.	2 x 35 2 x 55	4.45 3.00	14.7	
○□ CP40					