

MB Series



Specification

Mode of Operation	: Non - Maintaine
Lamp	: ungsten Halogen or Dichroic Halogen, with 180°adjustable sets and plastic-coveranti-dust
Main Supply	: AC 220 Volt, 50 Hz, 10% Single Phase
Construction	: Electro-Galvanized steel sheet 1 mm. with powder and stove enamel coated anti-rustepoxy corrosionproof or Standard ABS casing
Battery	: Sealed lead acid battery, based on ISO 9001, ISO 14001 certified and UL
Charger	: Solid state system automatic battery charger
Charging Period	: 20-24 Hours
Safety Features	: Low - High voltage cut-off, preventing battery over discharge and recharge AC fuse - preventing short circuit and overload for main incoming AC 220 Volt DC fuse - preventing short circuit and charging & load

**MB Series
Dichroic Halogen (square)**

MODEL	BATTERY	BULBS (Watt)	DURATION(Hrs. Mins) ₋ +10%	WEIGHT (Kgs)	DIMENSION W x L x H (cm)
MB 15	12V. 15Ah.	2 x 35	2.00	8.0	28.5 x 8.5 x 32.5
		2 x 50	1.25		
		2 x 55	1.15		
MB 18	12V. 18Ah.	2 x 35	2.30	8.1	
		2 x 50	1.40		
		2 x 55	1.30		
MB 21	12V. 21Ah.	2 x 35	2.50	9.6	
		2 x 50	2.00		
		2 x 55	1.50		
MB 24	12V. 24Ah.	2 x 35	3.15	10.0	
		2 x 50	2.15		
		2 x 55	2.00		
MB 26	12V. 26Ah.	2 x 35	3.30	12.4	
		2 x 50	2.30		
		2 x 55	2.15		

Tungsten Halogen Lamp (round)

MODEL	BATTERY	BULBS (Watt)	DURATION(Hrs. Mins) ₋ +10%	WEIGHT (Kgs)	DIMENSION W x L x H (cm)
MB 15	12V. 15Ah.	2 x 35	2.00	8.0	28.5 x 8.5 x 32.5
		2 x 50	1.25		
		2 x 55	1.15		
MB 18	12V. 18Ah.	2 x 35	2.30	8.1	
		2 x 50	1.40		
		2 x 55	1.30		
MB 21	12V. 21Ah.	2 x 35	2.50	9.6	
		2 x 50	2.00		
		2 x 55	1.50		
MB 24	12V. 24Ah.	2 x 35	3.15	10.0	
		2 x 50	2.15		
		2 x 55	2.00		
MB 26	12V. 26Ah.	2 x 35	3.30	12.4	
		2 x 50	2.30		
		2 x 55	2.15		