

# EXB Series

**Ceiling Type**  
EXB 303 FL/PL



**Recess Mount Type**  
EXB 303 FL/PL



**Box Type**  
EXB 111-112 (FL/PL)



## EXB Series

The EXB Exit Sign Light are decoratively designed for convenient operation with clear and bright in single or double side signs comply to E.I.T. and TIS. Standards. EXA xxx - without battery (220 VAC. Operation) EXB xxx - with battery

## Specification

Mode of Operation	: Maintained
Lamp	: Fluorescent or PL
Main Supply	: AC 220 Volt, 50 Hz, 10% - Single Phase
Construction	: Electro-Galvanized steel sheet 1 mm. with epoxy powder and stove enamel coated anti-rust corrosion proof or ABS Flame Retardant UL 94 V - O
Battery	: Sealed lead acid battery, based on ISO 9001, ISO 14001 certified and UL Nickle Metal Hydride battery, High Temperature type
Chargers	: Solid state system automatic battery charger
Charging Period	: 15-24 Hours as Required
Safety Features	: ♦ Low - High voltage cut-off, preventing battery over discharge and recharge ♦ AC fuse - preventing short circuit and overload for main incoming AC 220 Volt ♦ DC fuse - preventing short circuit and overload for charging
Legend	: ISO Green, other legend optional are available
Mounting	: Wall mounted or Ceiling mounted
Remarks	: EXA series without battery charger, safety Features and indicator display : Legend on clear acrylic are available